

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** LIQUID NAILS DIRECT STICK LOW ODOUR

**Recommended use of the chemical and restrictions on use:** Adhesive.

**Supplier:** Selleys New Zealand, a division of DuluxGroup (New Zealand) Pty Ltd  
ABN 55 133 404 118  
Co. 2355191

**Street Address:** The Gate Industrial Park,  
373 Neilson St, Onehunga  
Auckland, New Zealand

**Telephone Number:** +64 9 636 2850  
**Facsimile:** +64 9 636 2851  
**Emergency Telephone:** **0 800 734 607 (ALL HOURS)**

## 2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

**SIGNAL WORD:** DANGER

**Subclasses:**

- Subclass 6.3 Category A - Substances that are irritating to the skin.
- Subclass 6.4 Category A - Substances that are irritating to the eye.
- Subclass 6.5 Category A - Substances that are respiratory sensitisers.
- Subclass 6.5 Category B - Substances that are contact sensitisers.
- Subclass 6.9 Category A - Substances that are toxic to human target organs or systems.

Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006



**Hazard Statement(s):**

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H372 Causes damage to organs through prolonged or repeated exposure.

# Safety Data Sheet



## Precautionary Statement(s):

### Prevention:

P102 Keep out of reach of children.  
P103 Read label before use.  
P260 Do not breathe mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P285 In case of inadequate ventilation wear respiratory protection.

### Response:

P304+P341 IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.  
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).  
P363 Wash contaminated clothing before re-use.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P314 Get medical advice/attention if you feel unwell.

### Storage:

No storage statements.

### Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Filler(s)	-	30-60%	-
Polymeric MDI copolymer	53862-89-8	10-<30%	-
Isocyanic acid, polymethylene polyphenylene ester	9016-87-9	1-<10%	H332 H319 H335 H315 H351 H334 H317 H373
Diphenylmethane-4,4-diisocyanate MDI	101-68-8	1-<10%	H315 H317 H319 H332 H334 H335 H351 H373

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discoloration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

### Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Product Name: LIQUID NAILS DIRECT STICK LOW ODOUR  
Substance No: 000000022109

Issued: 13/01/2014  
Version: 2

# Safety Data Sheet

**Eye Contact:**

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

**Ingestion:**

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

**Indication of immediate medical attention and special treatment needed:**

Treat symptomatically. Effects may be delayed.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:**

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

**Specific hazards arising from the substance or mixture:**

Combustible liquid. On burning will emit toxic fumes, including those of hydrogen cyanide, isocyanates, oxides of carbon and oxides of nitrogen.

**Special protective equipment and precautions for fire-fighters:**

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency procedures/Environmental precautions:**

If contamination of sewers or waterways has occurred advise local emergency services.

**Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:**

**SMALL SPILLS:** Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

**LARGE SPILLS:** Work up wind or increase ventilation. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Scrape up excess material before cure. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Cured material can only be removed by cutting or abrasion.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Keep out of reach of children. Avoid skin and eye contact and breathing in vapour.

**Conditions for safe storage, including any incompatibilities:** Store in cool place and out of direct sunlight. Keep dry - reacts with water. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Workplace Exposure Standards:** No value assigned for this specific material by the New Zealand Department of Labour (Health & Safety). However, Workplace Exposure Standard(s) for constituent(s):

Isocyanates, all, (as -NCO): WES-TWA 0.02 mg/m<sup>3</sup>; WES-STEL 0.07 mg/m<sup>3</sup>, sen

# Safety Data Sheet



As published by the New Zealand Department of Labour (Health & Safety).

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

WES - STEL (Workplace Exposure Standard - Short Term Exposure Limits) - The 15 minute average exposure standard. Applies to any 15 minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both short-term and eight-hour, time-weighted average exposures should be determined.

'Sen' Notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

## Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Blue



MANUFACTURE, PACKAGING AND TRANSPORT: Blue - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and face shield or chemical goggles. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If inhalation risk exists due to processing vapours, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

FOR CONSUMER USE: When using the product as an adhesive or sealant: wear protective clothing, impervious gloves and safety glasses.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Paste
<b>Colour:</b>	Brown
<b>Solubility:</b>	Insoluble in water. Uncured material is soluble in organic solvents.
<b>Specific Gravity:</b>	1.45
<b>Relative Vapour Density (air=1):</b>	>1
<b>Vapour Pressure (20 °C):</b>	Not available
<b>Flash Point (°C):</b>	>100 (CC)
<b>Flammability Limits (%):</b>	Not available
<b>Autoignition Temperature (°C):</b>	Not available
<b>% Volatile by Weight:</b>	Not available

Product Name: LIQUID NAILS DIRECT STICK LOW ODOUR  
Substance No: 00000022109

Issued: 13/01/2014  
Version: 2

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Melting Point/Range (°C):</b>	Not applicable
<b>Boiling Point/Range (°C):</b>	242
<b>Decomposition Point (°C):</b>	Not available
<b>pH:</b>	Not applicable
<b>Viscosity:</b>	Not available
<b>Evaporation Rate:</b>	Not available

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	Reacts with moisture.
<b>Chemical stability:</b>	Stable under normal conditions of use.
<b>Possibility of hazardous reactions:</b>	Reacts with moisture liberating carbon dioxide.
<b>Conditions to avoid:</b>	Avoid contact with foodstuffs. Avoid exposure to moisture. Avoid exposure to heat, sources of ignition, and open flame.
<b>Incompatible materials:</b>	Incompatible with acids, alcohols, oxidising agents and moisture.
<b>Hazardous decomposition products:</b>	Hydrogen cyanide. Isocyanates. Oxides of carbon. Oxides of nitrogen.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion:</b>	Swallowing may result in nausea, vomiting, and abdominal pain.
<b>Eye contact:</b>	An eye irritant.
<b>Skin contact:</b>	Contact with skin will result in irritation. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
<b>Inhalation:</b>	Material is irritant to the mucous membranes of the respiratory tract (airways). A respiratory sensitizer. Can cause possible allergic reactions, producing asthma-like symptoms.

**Acute toxicity:** No LD50 data available for the product.

**Chronic effects:** No information available for the product. For Isocyanates: Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitizers including diisocyanates. These results emphasise the need for protective clothing including gloves to be worn when handling these chemicals or in maintenance work.

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	Avoid contaminating waterways.
--------------------	--------------------------------

## 13. DISPOSAL CONSIDERATIONS

## 13. DISPOSAL CONSIDERATIONS

### Disposal Methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

### Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

### Subclasses:

Subclass 6.3 Category A - Substances that are irritating to the skin.

Subclass 6.4 Category A - Substances that are irritating to the eye.

Subclass 6.5 Category A - Substances that are respiratory sensitisers.

Subclass 6.5 Category B - Substances that are contact sensitisers.

Subclass 6.9 Category A - Substances that are toxic to human target organs or systems.

Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006

### Hazard Statement(s):

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

## 16. OTHER INFORMATION

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)

Fax: 1300 555 305 (Australia wide)

Phone: 0800 735 539 (New Zealand)

Fax: 0800 804 583 (New Zealand)

### Reason(s) for Issue:

5 Yearly Revised Primary SDS

Change in Hazardous Substance Classification

# Safety Data Sheet



This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

DuluxGroup owns the Dulux trade mark in Australia, New Zealand, PNG and Fiji. It is not associated with and has no connection to the owners of the Dulux trade mark in other countries, nor does it sell Dulux products in other countries.