

Safety Data Sheet



1. Identification

Product Name: Duracrete EMT Hardener
Other Names:
Recommended use: Part B of two pack epoxy resin system
Supplier: Uroxsys Ltd
Street Address: 2 Stonedon Drive, East Tamaki, Auckland
Telephone Number: +64 9 2740808 (8.00am to 5.00pm, Monday to Friday)
Emergency Telephone: After hours phone CHEMCALL 0800 243622 (or +64 4 9179888)
National Poison Information Centre 0800 POISON (764766)
Date of issue 1 September 2022

2. Hazards identification

GHS classification of the substance/mixture:

Classified as Hazardous according to Hazardous Substances (Hazard Classification) Notice 2020
Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433: 2020
Transport of Dangerous Goods.



Skin corrosion Category 1B, Skin sensitisation Category 1, STOT (repeated exposure) Category 2

EPA Approval: HSR002658.

Surface Coatings and Colourants (Corrosive) Group Standard 2020
6.5B, 6.9B, 8.2B

Signal Word:

DANGER

Hazard Statements:

H314: Causes severe skin burns and serious eye damage

H317: May cause an allergic skin reaction.

H373: May cause damage to organs through prolonged or repeated exposure

Precautionary Statements – Prevention:

P102: Keep out of reach of children.

P103: Read label before use.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P264: Wash hands thoroughly after handling.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection.

Precautionary Statements – Response:

P101: If medical advice is needed, have product container or label at hand.
P303+P361+P353+P352: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water.
P304+P340+P310: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTRE/doctor.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary Statements – Storage:

P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.

Precautionary Statements – Disposal:

P501: Do not contaminate storm water with product or product washing. Do not pour product down the drain. Unwanted product should reacted with appropriate quantity of resin and be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via domestic recycling programmes may differ between local authorities. Check with your local council first.

3. Composition/information on ingredients

Material	CAS No	Content %
Benzyl alcohol	100-51-6	> 35
4,4'-Methylenebis(cyclohexanamine)	1761-71-3	< 35

4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

Ingestion:	If swallowed, rinse mouth. Do not induce vomiting. Seek medical advice.
Inhalation:	Move patient to fresh air. If breathing has stopped or is laboured give assisted respiration (e.g. mouth-to-mouth). Supplemental oxygen may be indicated. Seek medical advice. Prevent aspiration of vomit. Turn victim's head to the side
Skin Contact:	Remove contaminated clothing and shoes. Remove product and immediately flush affected area with water for at least 15 minutes. Seek medical advice.
Eye Contact:	Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lens if present and easy to do. Continue rinsing. Seek medical advice.

5. Fire-fighting measures

Hazards from combustion:	Corrosive substance
Fire-fighting advice:	On burning will emit toxic fumes including ammonia gas and nitrogen oxide gas. Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing. Do not allow run off to enter drains or water courses.
Suitable Extinguishing Media:	Foam, dry agent (carbon dioxide, dry chemical powder).
Hazchem Code	3X

6. Accidental release measures

Emergency procedures:	If contamination of sewers or waterways has occurred advise local emergency services.
Methods for containment & clean up:	Wear self-contained breathing apparatus and protective equipment to prevent skin and eye contamination and inhalation of vapours. Evacuate area. Contain - prevent runoff into drains and waterways. Use absorbent material (sand or earth). Collect and seal in properly labelled containers for disposal.

7. Handling and storage

Handling advice:	Avoid skin and eye contact and breathing in vapour. Keep out of reach of children.
Storage advice:	Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. Exposure controls/personal protection

Occupational Exposure Limits:	No value assigned for this specific material by Worksafe NZ.
Engineering Control Measures:	Ensure ventilation is adequate.
Personal Protective Equipment:	Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. Physical and chemical properties

Physical state:	Liquid
Solubility in water:	<0.1 g/l
Specific Gravity:	1.03
Flash Point (°C):	112°C
Flammability Limits (%):	Not available
Boiling Point/Range (°C):	207°C
Colour	Colourless

10. Stability and reactivity

Stability:	Stable at normal temperatures and storage conditions.
Incompatible materials:	Incompatible with strong acids and oxidizing agents.

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	May cause severe burning of the mouth and upper gastrointestinal tract with pain, bleeding, vomiting, diarrhea and decreased blood pressure.
Eye contact:	Causes burns. May cause eye corrosion with corneal or conjunctival ulceration. High concentrations of vapours will cause irritation.
Skin contact:	Causes burns or ulceration. May cause allergic skin rashes.
Inhalation:	Inhalational overexposure may cause nose, throat, or lung irritation.
Long term Effects:	Prolonged or repeated exposure may cause skin sensitization or other allergic response.
Toxicological Data:	Oral LD50 (rabbit): >2000 mg/kg, Inhalation LC50 (rabbit): 27.5 mg/l, Dermal LD50 (rabbit) >2110 mg/kg

12. Ecological information

Avoid contaminating waterways.

Benzyl alcohol LC50 (96 h):460 mg/l Lepomis macrochirus(Fish, freshwater)

4,4-Methylenebiscyclohexanamine LC50 (48 h) 38 mg/l Leuciscus idus (fish, freshwater)

13. Disposal considerations

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

Do not contaminate storm water with product or product washing. Do not pour product down the drain. Unwanted product should reacted with appropriate quantity of resin and be brushed out on newspaper, allowed

to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via domestic recycling programmes may differ between local authorities. Check with your local council first.

14. Transport information



Road and Rail Transport:

Classified as Dangerous Goods by NZS 5433 Transport of Dangerous Goods on Land.

UN No: 2735, Class-primary 8 Corrosive

Packing Group: II

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, NOS (4,4'-methylenebiscyclohexanamine)

Hazchem Code: 3X

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 2735, Class-primary: 8 Corrosive

Packing Group: II

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, NOS (4,4'-methylenebiscyclohexanamine)

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 2735, Class-primary: 8 Corrosive

Packing Group: II

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, NOS (4,4'-methylenebiscyclohexanamine)

15. Regulatory information

EPA Approval: HSR002658.

Surface Coatings and Colourants (Corrosive) Group Standard 2020

16. Other information

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.

This version replaces all previous versions.

END OF SDS