

1. Identification

Product Name: Marine Aliphatic Matt
Other Names:
Recommended use: Marine timber coating – matt finish
Supplier: Uroxsys Ltd
Street Address: 2 Stonedon Drive, East Tamaki, Auckland
Telephone Number: +64 9 2740808 (8.00am to 5.00pm, Monday to Friday)
Emergency Telephone: After hours phone CHEMCALL 0800 243622 (or +64 4 9179888)
National Poison Information Centre 0800 POISON (764766)
Date of issue 1st September 2022

2. Hazards identification

GHS classification of the substance/mixture:

Classified as Hazardous according to Hazardous Substances (Hazard Classification) Notice 2020
Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433: 2020
Transport of Dangerous Goods.



Flammable Liquid Category 3, Skin sensitisation Category 1, Eye irritation Category 2, Respiratory sensitisation Category 1, STOT (repeated exposure) Category 1, Aquatic toxicity (chronic) Category 2

EPA Approval: HSR002662

Surface Coatings and Colourants (Flammable) Group Standard 2020
3.1C, 6.1E(I), 6.4A, 6.5A, 6.5B, 6.9B, 9.1B

Signal Word:

DANGER

Hazard Statements:

H226: Flammable liquid and vapour.
H316: Causes mild skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H372: May cause damage to organs through prolonged or repeated exposure.
H411: Toxic to aquatic life with long lasting effects.

Precautionary Statements – Prevention:

P103: Read label before use.
P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P261: Avoid breathing fume/mist/vapours/spray.
P264: Wash hands thoroughly after handling.
P272: Contaminated work clothing should not be allowed out of the workplace
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P285: In case of inadequate ventilation wear respiratory protection.

Precautionary Statements – Response:

P101: If medical advice is needed, have product container or label at hand.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P304+P341: IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314: Get medical advice/attention if you feel unwell.
P332+P313: If skin irritation occurs: Get medical advice/ attention.
P337+P331: If eye irritation persists: Get medical advice/attention.
P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P363: Wash contaminated clothing before reuse.
P370+P378: In case of fire: use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder) for extinction.

Precautionary Statements – Storage:

P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.

Precautionary Statements – Disposal:

P501: Do not let product enter the environment. Do not dispose of in waterways or sewers. Unwanted product should be brushed out on newspaper, allowed to cure and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to cure. When cured, recycle the container via recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

3. Composition/information on ingredients

Material	CAS No:	Content %
Isocyanate prepolymers		10 - 25%
Aromatic hydrocarbon solvent	64742-95-6	10 - 25%
1-methoxy-2-propyl acetate	108-65-6	10 - 25%
2-Propanol, 1-methoxy-, propanoate	148462-57-1	10 - 25%
Ethylene glycol butyl ether acetate	112-07-2	10 - 25%
Hexamethylene diisocyanate Homopolymer	28182-81-2	2.5-10%
Isophorone diisocyanate homopolymer	53880-05-0	<6%
Tosyl isocyanate	4083-64-1	<1%
Bis(pentamethyl-4-piperidyl) sebacate	41556-26-7	<1%

Hydroxyphenyl-benzotriazole derivatives	112945-52-5	<1%
Hexamethylene-1,6- diisocyanate	822-06-0	<0.05%
Isophorone diisocyanate	4098-71-9	<0.05%
Xylene	1330-20-7	<2.5%

4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766. In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person.

Ingestion:	If swallowed, do NOT induce vomiting. Immediately rinse mouth with water and give water to drink. Seek immediate medical assistance.
Inhalation:	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms or feel unwell: Call a POISON CENTER or doctor/physician.
Skin Contact:	IF on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/ attention. Wash contaminated clothing before reuse.
Eye Contact:	If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Notes to physician:	Treat symptomatically.

5. Fire-fighting measures

Hazards from combustion:	On burning may emit toxic fumes including those of carbon monoxide, carbon dioxide, smoke, nitrogen oxides and isocyanate vapours.
Fire-fighting advice:	Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.
Suitable Extinguishing Media:	Water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder). Do not use water jet.
Hazchem Code	3[Y]

6. Accidental release measures

Emergency procedures:	Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering. If contamination of sewers or waterways has occurred advise local emergency services.
Methods for containment & clean up:	Quickly wipe up material before it cures, with cloth or absorbent paper avoiding skin contact. Uncured material will dissolve in a 50:50 mixture of acetone and meths. Cured material can only be removed by abrasion.
For large spills:	Ventilate the area and avoid breathing vapours. Wear protective equipment to prevent skin and eye contamination and inhalation of vapours. Contain and absorb spillage with non combustible materials e.g. sand, earth vermiculate. Scrape up material before it cures. Collect in properly labeled containers and seal once product has hardened.

Wash area down with excess water. Cured material can only be removed by abrasion.

7. Handling and storage

Handling advice:	Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in processes in which this product is used. Avoid skin and eye contact and breathing in vapour. May form flammable vapour mixtures with air. All potential sources of ignition must be eliminated both in and near the work area. Do NOT smoke. Flameproof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed. Vapour may travel a considerable distance to a source of ignition and flash back.
Storage advice:	Store in a cool place and out of direct sunlight. Store away from acids, alcohols, oxidizing agents, moisture and sources of heat or ignition. Keep dry, reacts with water; may lead to drum rupture. Keep containers tightly closed at all times, check regularly for leaks. Prevent unauthorized access.

8. Exposure controls/personal protection

Occupational Exposure Limits:	No value assigned for this specific material by Worksafe NZ. However, NZ Workplace Exposure Standard(s) for constituent(s): Isocyanates, all (as-NCO): TWA 0.02 mg/m ³ ; STEL 0.07 mg/m ³ . These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust. Xylene: TWA 50ppm, 217 mg/m ³
Engineering Control Measures:	Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected.
Personal Protective Equipment:	Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. Physical and chemical properties

Physical state:	Viscous liquid
Solubility:	Insoluble in water. Soluble in organic solvents.
Specific Gravity:	0.98
Flash Point (°C):	40°C
Flammability Limits (%):	LEL: 1.1 UEL: 6.0 (xylene)
Boiling Point/Range (°C):	126
Colour	Pale yellow

10. Stability and reactivity

Stability:	Stable under normal conditions
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition and open flame. Reacts with moisture
Incompatible materials:	Incompatible with oxidizing agents, strong acids and bases.

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.
Eye contact:	An eye irritant.
Skin contact:	Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.
Inhalation:	Material may be irritant to the mucous membranes of the respiratory tract (airways). May cause respiratory sensitization in sensitive individuals, producing asthma-like symptoms. Breathing in vapour can result in headaches, dizziness and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgment and if exposure is prolonged, unconsciousness.
Long Term Effects:	No information available for the product. For the solvent evidence indicates that repeated or prolonged exposure to this chemical could result in central nervous system disorders.
Toxicological Data:	No LD50 data available for the product. The toxicity of the product may be attributed to the solvents it contains. Additive effects may occur with mixtures of solvents. Similar effects can occur where the consumption of alcohol is also involved. However, for constituent Aromatic hydrocarbon solvent: Oral LD50 (rat): 6800 mg/kg, Dermal LD50 (rabbit): 3400 mg/kg, Inhalation LC50 (rat): 1320 ppm/6 Hrs/90 days Ethylene glycol butyl ether acetate: Oral LD50 (rat) 1600 mg/kg, Dermal LD50 (rabbit) 1480 mg/kg 1-methoxy-2-propyl acetate: Oral LD50 (rat) 8532mg/kg, Dermal LD50 (rabbit) 5000 mg/kg HDI homopolymer: Oral LD 50 (rat) 18500 mg/kg Xylene: Oral LD 50 (mouse) 1590 mg/l, Inhalation LC50 (rat) 6350 ppm Isophorone diisocyanate: Inhalation LC50 (rat) 0.67 mg/l, Oral LD50 (rat) 1270 mg/kg, Dermal LD50 (rabbit) 4780 mg/kg Hexamethylene diisocyanate: Inhalation dust/mist: LC50 30 mg/l, Oral LD50 (mouse) 350mg/kg, Dermal LD50 (rabbit) 593 mg/kg 2-Propanol, 1-methoxy -, propanoate: Oral LD50 (rat) 12565 mg/kg, Dermal LD50 (rabbit) 11890 mg/kg Bis(pentamethyl-4-piperidyl)sebacate: Oral LD50 (rat) 2615 mg/kg

12. Ecological information

Avoid contaminating waterways. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. For constituent

Aromatic hydrocarbon solvent: Acute toxicity – Fish:LL/EL/IL50: 1-10 mg/l, Algae:1-10mg/l, Aquatic invertebrates: 1-10 mg/l, microorganisms 10-100mg/l

1-methoxy-2-propyl acetate: Acute Toxicity – Fish: LC50 (Oncorhynchus mykiss): 134 mg/l/96h

Daphnia EC50 (Daphnia magna): 408 mg/l/48h, Algae ErC50 (Pseudokirchneriella subcapitata): >1000 mg/l/96h

2-Propanol, 1-methoxy-, propanoate: >5000mg/l Goldfish, 96hr LC50 fish mg/l, 100mg/l Daphnia magna 48hr EC50 crustacea,

Ethylene glycol butyl ether acetate: 37mg/l Daphnia magna 48hr EC50 crustacea,

HDI Homopolymer: 100mg/l Danio rerio 96hr LC50 fish mg/l, 100mg/l Daphnia magna 48hr EC50 crustacea,

Bis(pentamethyl-4-piperidyl) sebacate 1mg/l Lepomis macrochirus 96hr LC50 fish mg/l, 20mg/l Daphnia magna 48hr EC50 crustacea,

Xylene: 3.3mg/l Oncorhynchus mykiss 96hr LC50 fish mg/l, 20mg/l Daphnia magna 48hr EC50 crustacea

13. Disposal considerations

Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

Empty container:

Do not let product enter the environment. Do not dispose of in waterways or sewers. Unwanted product should be brushed out on newspaper, allowed to cure and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to cure. When cured, recycle the container via recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

14. Transport information

Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433: 2020 Transport of Dangerous Goods.



Road and Rail Transport

Classified as Dangerous Goods by NZS 5433 Transport of Dangerous Goods on Land.

UN No: 1263

Class-primary 3 Flammable Liquid,Packing Group: III

Proper Shipping Name: PAINT, Hazchem Code: 3[Y]

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1263
Class-primary: 3 Flammable Liquid
Packing Group: III
Proper Shipping Name: PAINT, EMS: F-E, S-E

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1263
Class-primary: 3 Flammable Liquid
Packing Group: III
Proper Shipping Name: PAINT

15. Regulatory information

EPA Approval:HSR002662, Surface Coatings and Colourants (Flammable) Group Standard 2020

16. Other information

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.

This version replaces all previous versions.

END OF SDS