



TECHNICAL DATA

POLYURETHANE SPRAY THINNER

DESCRIPTION	A low flash point solvent blend for nominated Uroxsys polyurethanes.	
USES	For adjusting the viscosity of mixed Uroxsys sprayable polyurethanes to the recommended spray viscosity.	
COLOUR	Clear	
FEATURES	Water white Fast flash off Excellent solvency	
APPLICATION	Use as directed on individual product labels or technical data sheets.	
TECHNICAL DATA	Appearance:	Colourless liquid
	Specific Gravity:	0.84
	Flash Point:	-4°C
	UN No.:	1992
	DG Class:	3
	Haz. Chem Code:	3[Y]E
	Toxic Substances Schedule:	Standard Poison
	Packaging:	4l, 20l

SAFETY DATA: Flammable liquid. Use in well ventilated areas only. Avoid breathing vapour. Can cause irritation. Wear protective clothing including gloves. For detailed information, consult the Material Safety Data Sheet, available on request from Uroxsys Ltd.

This information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

PUSpray, TD3 JAN22