

Safety Data Sheet



1. Identification

Product Name: Reducer R122
Other Names:
Recommended use: Polyurethane Thinner
Supplier: Uroxsys Ltd
Street Address: 2 Stonedon Drive, East Tamaki, Auckland
Telephone Number: +64 9 2740808 (8.00am to 5.00pm, Monday to Friday)
Emergency Telephone: After hours phone CHEMCALL 0800 243622 (or +64 4 9179888)
National Poison Information Centre 0800 POISON (764766)
Date of issue 1st September 2022

2. Hazards identification

GHS classification of the substance/mixture:

Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433: 2020 Transport of Dangerous Goods.



Flammable Liquid Category 3, Skin Irritation Category 3, Eye irritation Category 2, STOT (repeated exposure) Category 1, Aquatic toxicity (chronic) Category 2

EPA Approval: HSR002650.

Solvents (Flammable) Group Standard 2020

3.1C, 6.1E(I), 6.3B, 6.4A, 6.9A, 9.1B

Signal Word:

DANGER

Hazard Statements:

H226: Flammable liquid and vapour.

H316: Causes mild skin irritation.

H319: Causes serious eye irritation.

H372: May cause damage to organs through prolonged or repeated exposure

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statements – Prevention:

- P102: Keep out of reach of children.
- P103: Read label before use.
- P210: Keep away from sparks/open flames/hot surfaces. No smoking.
- P233: Keep container tightly closed.
- P240: Ground/bond container and receiving equipment.
- P241: Use explosion-proof electrical/ventilating/lighting equipment.
- P242: Use only non-sparking tools.
- P243: Take precautionary measures against static discharge.
- P260: Do not breathe fume/gas/mist/vapours/spray.
- P264: Wash hands thoroughly after handling.
- P273: Avoid release to the environment.
- P280: Wear protective gloves/eye protection/face protection.

Precautionary Statements – Response:

- P101: If medical advice is needed, have product container or label at hand.
- P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P314: Get medical advice/attention if you feel unwell.
- P332+P313: If skin irritation occurs: Get medical advice/ attention.
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P370+P378: In case of fire: Use dry powder, foam, carbon dioxide for extinction.
- P391: Collect spillage.

Precautionary Statements – Storage:

- P403+P235: Store in a well-ventilated place. Keep cool.
- P405: Store locked up.

Precautionary Statements – Disposal:

P501: Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via domestic recycling programmes may differ between local authorities. Check with your local council first.

3. Composition/information on ingredients

Material	CAS No	Content %
Aromatic hydrocarbon solvent	64742-95-6	40 – 60
1-methoxy-2-propyl acetate	108-65-6	40 – 60

4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

- Ingestion: If swallowed, do NOT induce vomiting. Immediately rinse mouth with water and give water to drink. Seek immediate medical assistance.
- Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Notes to physician: Treat symptomatically.

5. Fire-fighting measures

Hazards from combustion: Flammable liquid. On burning will emit toxic fumes including those of oxides of carbon.

Fire-fighting advice: On burning will emit toxic fumes. If safe to do so, remove containers from the path of fire. Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media: Foam, dry agent (carbon dioxide, dry chemical powder).
Hazchem Code 3[Y]

6. Accidental release measures

Emergency procedures: If contamination of sewers or waterways has occurred advise local emergency services.

Methods for containment & clean up: Shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. Handling and storage

Handling advice: Avoid skin and eye contact and breathing in vapour. May form flammable vapour mixtures with air. All potential sources of ignition must be eliminated both in and near the work area. Do NOT smoke. Flameproof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed. Vapour may travel a considerable distance to a source of ignition and flash back.

Storage advice: Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. Exposure controls/personal protection

Occupational Exposure Limits:	No value assigned for this specific material by Worksafe New Zealand.
Engineering Control Measures:	Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected.
Personal Protective Equipment:	Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. Physical and chemical properties

Physical state:	Liquid
Solubility in water:	Insoluble in water
Specific Gravity:	0.92
Flash Point (°C):	45°C
Flammability Limits (%):	1.5-7.0
Boiling Point/Range (°C):	143-149
Colour	Colourless

10. Stability and reactivity

Stability:	Stable under normal conditions
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition and open flame.
Incompatible materials:	Incompatible with oxidising agents
Hazardous decomposition products:	Oxides of carbon

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is uncoordinated there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.
Eye contact:	An eye irritant.
Skin contact:	Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.

Inhalation: Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

Long term Effects: No information available for the product.

Toxicological Data: No LD50 data available for the product. The toxicity of the product may be attributed to the solvents it contains.

Additive effects may occur with mixtures of solvents. Similar effects can occur where the consumption of alcohol is also involved. However, for constituent Aromatic hydrocarbon solvent: Oral LD50 (rat): 6800 mg/kg, Dermal LD50 (rabbit): 3400 mg/kg, Inhalation LC50 (rat): 1320 ppm/6 Hrs/90 days
1-methoxy-2-propyl acetate: Oral LD50 (rat) 8532 mg/kg, Dermal LD50 (rabbit) 5000 mg/kg

12. Ecological information

Avoid contaminating waterways. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

For constituent

Aromatic hydrocarbon solvent: Acute toxicity – Fish:LL/EL/IL50: 1-10 mg/l, Algae:1-10mg/l, Aquatic invertebrates: 1-10 mg/l, microorganisms 10-100mg/l

1-methoxy-2-propyl acetate: Acute Toxicity – Fish: LC50 (Oncorhynchus mykiss): 134 mg/l/96h

Daphnia EC50 (Daphnia magna): 408 mg/l/48h, Algae ErC50 (Pseudokirchneriella subcapitata): >1000 mg/l/96h

13. Disposal considerations

Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

Empty container: Do not contaminate storm water with product or product washing. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via domestic recycling programmes may differ between local authorities. Check with your local council first.

14. Transport information

Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433: 2020 Transport of Dangerous Goods.



Road and Rail Transport

Classified as Dangerous Goods by NZS 5433 Transport of Dangerous Goods on Land.

UN No: 1263

Class-primary 3 Flammable Liquid

Packing Group: III

Proper Shipping Name: PAINT RELATED MATERIAL

Hazchem Code: 3[Y]

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1263

Class-primary: 3 Flammable Liquid

Packing Group: III

Proper Shipping Name: PAINT RELATED MATERIAL

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1263

Class-primary: 3 Flammable Liquid

Packing Group: III

Proper Shipping Name: PAINT RELATED MATERIAL

15. Regulatory information

EPA Approval: HSR002650. Solvents (Flammable) Group Standard 2020

16. Other information

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.

This version replaces all previous versions.

END OF SDS