



TECHNICAL DATA

DURACOAT RIMU SEALER

URETHANE TIMBER PRIMER

DESCRIPTION	Duracoat Rimu Sealer is a clear, two-component polyurethane primer, with fast tack-free and early easy sanding characteristics.
USES	Duracoat Rimu Sealer is intended for use in sealing and priming timbers such as Rimu, for subsequent overcoating with polyurethane or acid catalysed finish coatings.
COLOUR	Clear.
SURFACE PREPARATION	Surfaces to be sanded and dust-free.
APPLICATION	By airless spray or conventional spray at recommended coverage rate. Thinning should not be required.
TECHNICAL DATA	<p>2 component: Shake Resin component vigorously before decanting. Measure out the Resin and Hardener in the ratio of 2 parts Resin to 1 part Hardener by volume. Mix thoroughly.</p> <p>Film Thickness: 25 microns per coat DFT Theoretical</p> <p>Coverage Rate: 10 m² per litre on smooth surface</p> <p>Shelf Life: One year in sealed containers.</p> <p>Pot Life: 4 hours @ 20°C</p> <p>Tack Free: 15 minutes @ 20°C</p> <p>Dry to Sand: 30 minutes @20°C</p> <p>Clean up: RT101 Gunwash or Uroxsys Polyurethane Brush Cleaner.</p>
SAFETY DATA:	<p>Wear protective clothing. Gloves are essential. Avoid contact with exposed skin. Contains isocyanates. When sprayed, this product may be harmful by inhalation. Do not breathe vapour or spray. Avoid contact with skin and eyes. Wear suitable protective clothing, gloves, eye and face protection, including suitable breathing protection, such as an air-supplied respirator or hood.</p>

This information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

D8013 TD7 JAN22