



TECHNICAL DATA

UVTEC WINDOW SYSTEM

CLEAR ALIPHATIC POLYURETHANE

DESCRIPTION AND USES

A moisture curing, aliphatic (non-yellowing), clear urethane coating for in situ application. Optimised for application to domestic and commercial windows to restrict the transmission of UV light.

FEATURES

Clear unobtrusive bonded coating
Non-yellowing moisture curing polyurethane
Contains protective UV absorbers
Fast curing over a wide temperature range
Comparatively low smell (xylene free)

SURFACE PREPARATION

In accordance with UVTEC Application manual.

APPLICATION

In accordance with UVTEC Application manual, UVTEC application procedures must be followed.

TECHNICAL DATA

Composition:	Aliphatic polyurethane prepolymer.
Gloss Level:	Approximately 90% at 60°
Final Cure:	7 days
Shelf Life:	12 months in factory sealed containers
Number of Coats:	Usually one coat on properly prepared and primed glass
Clean Up:	Uroxsys Polyurethane Brush Cleaner

SAFETY DATA

Contains isocyanates. When sprayed, this product may be harmful by inhalation. Do not breathe vapour or spray. Avoid contact with skin and eyes. Wear suitable protective clothing, gloves, eye and face protection, including suitable breathing protection, such as an air-supplied respirator or hood. Avoid contact with exposed skin.

DISCLAIMER: This information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

UVTEC TD3 JAN22