

Safety Data Sheet



1. Identification of the substance/mixture and supplier

Product Name: Duracoat ZK Gloss Resin
Other Names:
Recommended use: Two pack polyurethane coating.
Supplier: Uroxsys Ltd
Street Address: 2 Stonedon Drive, East Tamaki, Auckland
Telephone Number: +64 9 2740808 (8.00am to 5.00pm, Monday to Friday)
Facsimile: +64 9 2740500
Emergency Telephone: After hours phone 0800 867666 (or 09 3034580), quote reference:
Uroxsys Helpline
National Poison Information Centre 0800 POISON (764766)
Date of issue 8 May 2019

2. Hazards identification

DANGER



3.1B, 6.1D (Oral), 6.1D (Inhalation), 6.3B, 6.4A, 6.7B, 6.8B, 6.9B, 9.1D, 9.2D, 9.3C
EPA Approval: HSR002662

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2017
Classified as Dangerous Goods by NZS 5433 Transport of Dangerous Goods on Land.

Hazard Statements:

H225: Highly flammable liquid and vapour.
H302: Harmful if swallowed.
H316: Causes mild skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H351: Suspected of causing cancer
H361: Suspected of damaging fertility or the unborn child
H373: May cause damage to organs through prolonged or repeated exposure
H413: May cause long lasting harmful effects to aquatic life.
H423: Harmful to the soil environment.
H433: Harmful to terrestrial vertebrates.

Prevention Statements

- P102: Keep out of reach of children.
- P103: Read label before use.
- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from sparks/open flames/hot surfaces. No smoking.
- P233: Keep container tightly closed.
- P240: Ground/bond container and receiving equipment.
- P241: Use explosion-proof electrical/ventilating/lighting equipment.
- P242: Use only non-sparking tools.
- P243: Take precautionary measures against static discharge.
- P260: Do not breathe dust/fume/gas/mist/vapours/spray.
- P261: Avoid breathing fume/gas/mist/vapours/spray.
- P264: Wash hands thoroughly after handling.
- P270: Do not eat, drink or smoke when using this product.
- P271: Use only outdoors or in a well-ventilated area.
- P273: Avoid release to the environment.
- P280: Wear protective gloves/eye protection/face protection.
- P281: Use personal protective equipment as required. (*see section 8*)

Response Statements

- P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313: IF exposed or concerned: Get medical advice/ attention.
- P312: Call a POISON CENTER or doctor/physician if you feel unwell.
- P314: Get medical advice/attention if you feel unwell.
- P330: Rinse mouth.
- P332+P313: If skin irritation occurs: get medical advice/attention.
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P370+P378: In case of fire: use water fog (or if unavailable fine water spray), foam or dry agent (carbon dioxide, dry chemical powder) for extinction.

Storage Statements

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405: Store locked up.

Disposal Statements

P501: Do not let product enter the environment. Do not dispose of in waterways or sewers. Do not contaminate storm water with product or product washing. Do not pour product down the drain. Unwanted product should reacted with appropriate quantity of hardener and be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via domestic recycling programmes may differ between local authorities. Check with your local council first.

3. Composition/information on ingredients

Material	CAS No	%
Toluene	108-88-3	30 – 60
Synthetic resin		10 – 30
Xylene	1330-20-7	10 – 30
Propylene carbonate	108-32-7	0 – 10
Aromatic hydrocarbon solvent	64742-95-6	< 0.5

4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

Ingestion:	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.
Inhalation:	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
Skin Contact:	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: get medical advice/attention.
Eye Contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Notes to physician:	Treat symptomatically.

5. Fire-fighting measures

Hazards from combustion:	On burning may emit toxic fumes.
Fire-fighting advice:	Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.
Suitable Extinguishing Media:	In case of fire: use water fog (or if unavailable fine water spray), foam or dry agent (carbon dioxide, dry chemical powder) for extinction.
Hazchem Code	3[Y]

6. Accidental release measures

Emergency procedures:	If contamination of sewers or waterways has occurred advise local emergency services.
Methods for containment & clean up:	Quickly wipe up material with cloth or absorbent paper avoiding skin contact.
For large spills:	Shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect in properly labeled containers.

7. Handling and storage

Handling advice:	Avoid skin and eye contact and breathing in vapour. May form flammable vapour mixtures with air. All potential sources of ignition must be eliminated both in and near the work area. Do NOT smoke. Flameproof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed. Vapour may travel a considerable distance to a source of ignition and flash back.
Storage advice:	Store in a cool place and out of direct sunlight. Store away from acids, alcohols, oxidizing agents, moisture and sources of heat or ignition. Keep dry, reacts with water; may lead to drum rupture. Keep containers closed at all times, check regularly for leaks.

8. Exposure controls/personal protection

Occupational Exposure Limits:	No value assigned for this specific material by Worksafe NZ. However, NZ Workplace Exposure Standard(s) for constituent(s): xylene: TLV/TWA 50 ppm, 217 mg/m ³ toluene TLV/TWA 50 ppm (188 mg/m ³) skin
Engineering Control Measures:	Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected.
Personal Protective Equipment:	Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. Physical and chemical properties

Physical state:	Clear liquid
Solubility:	Negligible
Specific Gravity:	0.90-1.00
Flash Point (°C):	7°C
Flammability Limits (%):	1.2 – 8.0
Boiling Point/Range (°C):	110
Colour	Pale yellow

10. Stability and reactivity

Stability:	Stable under normal conditions
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition and open flame.
Incompatible materials:	Incompatible with oxidizing agents.

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Aspiration into the lungs may cause chemical pneumonitis which can be fatal.
Eye contact:	An eye irritant.
Skin contact:	Harmful in contact with skin. Prolonged contact with skin may cause dermatitis due to defatting.
Inhalation:	Vapour is irritating to respiratory tract. At high concentrations vapour may be absorbed and cause systemic effects such as nausea, dizziness and narcosis.
Long Term Effects:	Repeated exposure may affect the liver, kidneys and central nervous system. May cause slight foetotoxicity at doses which are maternally toxic. Prolonged or repeated contact may cause defatting of the skin which can lead to dermatitis.
Toxicological Data:	No LD50 data available for the product. The toxicity of the product may be attributed to the solvents it contains. Additive effects may occur with mixtures of solvents. Similar effects can occur where the consumption of alcohol is also involved. However, for constituent: Toluene: Oral LD50 (rat) 636 mg/kg, Inhalation LC50 (rat) 12.5-28.8 mg/l Xylene: Oral LD50 (mouse) 1590 mg/kg, Inhalation LC50 (rat) 6350 ppm Aromatic hydrocarbon solvent: Oral LD50 (rat): 6800 mg/kg, Dermal LD50 (rabbit): 3400 mg/kg, Inhalation LC50 (rat): 1320 ppm/6 Hrs/90 days

12. Eco toxicological information

Avoid contaminating waterways. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

Aromatic hydrocarbon solvent: Acute toxicity – Fish:LL/EL/IL50: 1-10 mg/l, Algae:1-10mg/l, Aquatic invertebrates: 1-10 mg/l, microorganisms 10-100mg/l

Xylene: 3.3mg/l Oncorhynchus mykiss 96hr LC50 fish mg/l, 20mg/l Daphnia magna 48hr EC50 crustacea

13. Disposal considerations

Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

Empty container: Do not let product enter the environment. Do not dispose of in waterways or sewers. Do not contaminate storm water with product or product washing. Do not pour product down the drain. Unwanted product should reacted with appropriate quantity of hardener and be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via domestic recycling programmes may differ between local authorities. Check with your local council first

14. Transport information



Road and Rail Transport

Classified as Dangerous Goods by NZS 5433 Transport of Dangerous Goods on Land.

UN No: 1263

Class-primary 3 Flammable Liquid

Packing Group: II

Proper Shipping Name: PAINT

Hazchem Code: 3[Y]E

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1263

Class-primary: 3 Flammable Liquid

Packing Group: II, Proper Shipping Name: PAINT

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1263

Class-primary: 3 Flammable Liquid

Packing Group: II, Proper Shipping Name: PAINT

15. Regulatory information

ERMA Approval: HSR002662

Group Standard: Surface Coatings and Colourants (Flammable) Group Standard

16. Other information

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.

This version replaces all previous versions.

END OF SDS

