



# Material Safety Data Sheet

## 1. Identification of the substance/mixture and supplier

Product Name: **Duracoat ZK Matt Resin**

Recommended use: Two pack polyurethane coating.

Supplier: Uroxsys Ltd  
Street Address: 2 Stonedon Drive, East Tamaki, Auckland  
Telephone Number: +64 9 2740808  
Facsimile: +64 9 2740500  
Emergency Telephone: After hours phone 0800 867666 (or 09 3034580), quote reference: Uroxsys Helpline  
ERMA Approval: HSR002662

## 2. Hazards identification

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001  
Classified as Dangerous Goods by NZS 5433:1999 Transport of Dangerous Goods on Land.

Subclass 3.1 Category C (medium hazard) - Flammable liquid  
Subclass 6.1 Category D - Substances which are acutely toxic.  
Subclass 6.3 Category A - Substances that are irritating to the skin.  
Subclass 6.4 Category A - Substances that are irritating to the eye

Risk phrases: R10 Flammable  
R36 Irritating to eyes  
R65 Harmful: May cause lung damage if swallowed

Safety Phrases S16 Keep away from sources of ignition - No smoking  
S24/25 Avoid contact with skin and eyes  
S28 After contact with skin, wash immediately with plenty of soap and water.  
S29 Do not empty into drains  
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

## 3. Composition/information on hazardous ingredients

Synthetic resin		10-30%	-
Xylene	1330-20-7	10-30%	R10,R20/21,R38
n-butyl acetate	123-86-4	10-30%	R10,R66,R67
1-methoxy-2-propyl acetate	108-65-6	<10%	R10, R36

## 4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

**Ingestion:** Do NOT induce vomiting. Seek immediate medical assistance. Begin artificial respiration if breathing has stopped. Use mouth to nose rather than mouth to mouth.

**Inhalation:** Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Get to a hospital or doctor quickly.

**Skin Contact:** If skin contact occurs, immediately remove contaminated clothing and wash skin thoroughly using soap if available. If irritation occurs seek medical advice.

**Eye Contact:** If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

**Notes to physician:** None available

## 5. Fire-fighting measures

**Hazards from combustion:** On burning may emit toxic fumes.

**Fire-fighting advice:** Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Flammable liquid. May form flammable vapour mixtures with air. Avoid all ignition sources. Heating can cause expansion or decomposition of the material, which can lead to the containers exploding. If safe to do so, remove containers from the path of fire. Keep containers cool with water spray.

**Suitable Extinguishing Media:** Foam, dry agent (carbon dioxide, dry chemical powder).

**Hazchem Code:** 3[Y]

## 6. Accidental release measures

### Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

### Methods for containment & clean up:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect in properly labeled containers.

## 7. Handling and storage

### Handling advice:

Avoid skin and eye contact and breathing in vapour. May form flammable vapour mixtures with air. All potential sources of ignition must be eliminated both in and near the work area. Do NOT smoke. Flameproof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed. Vapour may travel a considerable distance to a source of ignition and flash back.

### Storage advice:

Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

## 8. Exposure controls/personal protection

### Occupational Exposure Limits:

No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for constituent(s):

xylene: TLV/TWA 50 ppm, 217 mg/m<sup>3</sup>

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

WES - STEL (Workplace Exposure Standard - Short Term Exposure Limits) - The 15 minute average exposure standard. Applies to any 15 minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both short-term and eight hour, time-weighted average exposures should be determined.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

**Engineering Control Measures:**

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected.

**Personal Protective Equipment:**

Avoid breathing the vapour or spray mist. Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If spraying or there is an inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Avoid breathing dust when sanding, use a dust mask. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

**9. Physical and chemical properties**

Physical state:	Clear liquid
Colour:	Colourless
Solubility:	Negligible
Specific Gravity:	0.98
Flash Point (°C):	24°C
Flammability Limits (%):	1.1-6.6
Boiling Point/Range (°C):	138°C

**10. Stability and reactivity**

<b>Stability:</b>	Stable under normal conditions.
<b>Conditions to avoid:</b>	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition and open flame.
<b>Incompatible materials:</b>	Incompatible with oxidising agents

**11. Toxicological information**

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion:</b>	Aspiration into the lungs may cause chemical pneumonitis which can be fatal.
<b>Eye contact:</b>	An eye irritant.
<b>Skin contact:</b>	Harmful in contact with skin. Prolonged contact with skin may cause dermatitis due to defatting.
<b>Inhalation:</b>	Vapour is irritating to respiratory tract. At high concentrations vapour may be absorbed and cause systemic effects such as nausea, dizziness and narcosis.

**Long Term Effects:**

Not expected to be a skin sensitiser. Repeated exposure affects the respiratory and nervous systems of rats. Mays cause slight foetotoxicity in rats at doses which are maternally toxic.

**Toxicological Data:**

No LD50 data available for the product. The toxicity of the product may be attributed to the solvents it contains.

Additive effects may occur with mixtures of solvents. Similar effects can occur where the consumption of alcohol is also involved. However, for constituent xylene:

Oral LD50 (rat): >2000 mg/kg, Dermal LD50 (rat): >2000 mg/kg, Inhalation LC50 (rat): >5 mg/l

## 12. Ecotoxicological information

Avoid contaminating waterways.

## 13. Disposal considerations

Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

## 14. Transport information

### Road and Rail Transport

Classified as Dangerous Goods by NZS 5433:1999 Transport of Dangerous Goods on Land.

UN No: 1263

Class-primary 3 Flammable Liquid

Packing Group: III

Proper Shipping Name: PAINT RELATED MATERIAL

Hazchem Code: 3[Y]

### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1263

Class-primary: 3.3 Flammable Liquid

Packing Group: III

Proper Shipping Name: PAINT RELATED MATERIAL

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1263

Class-primary: 3 Flammable Liquid

Packing Group: III

Proper Shipping Name: PAINT RELATED MATERIAL

## 15. Regulatory information

Classification: This material is hazardous according to the criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

Subclass 3.1 Category C (medium hazard) - Flammable liquid

Subclass 6.1 Category D - Substances which are acutely toxic.

Subclass 6.3 Category A - Substances that are irritating to the skin.

Subclass 6.4 Category A - Substances that are irritating to the eye

## 16. Other information

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.