



Material Safety Data Sheet

1. Identification of the substance/mixture and supplier

Product Name: **Reactive Primer**

Recommended use: Primer

Supplier: Uroxsys Ltd

Street Address: 2 Stonedon Drive, East Tamaki, Auckland

Telephone Number: +64 9 2740808

Facsimile: +64 9 2740500

Emergency Telephone: After hours phone 0800 867666 (or 09 3034580), quote reference: Uroxsys Helpline

ERMA Approval: HSR002662

2. Hazards identification

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001
Classified as Dangerous Goods by NZS 5433:1999 Transport of Dangerous Goods on Land.

Subclass 3.1 Category B (high hazard) - Flammable liquid

Subclass 6.1 Category D - Substances which are acutely toxic.

Subclass 6.3 Category A - Substances that are irritating to the skin.

Subclass 6.4 Category A - Substances that are irritating to the eye

Subclass 6.5 Category A - Substances that are respiratory sensitisers

Subclass 6.5 Category B - Substances that are contact sensitisers

Risk phrases: R11 Highly Flammable
R36 Irritating to eyes
R65 Harmful: May cause lung damage if swallowed

Safety Phrases S16 Keep away from sources of ignition - No smoking
S24/25 Avoid contact with skin and eyes
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29 Do not empty into drains
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

3. Composition/information on hazardous ingredients

Toluene	108-88-3	30-60%	R11,R22
Isocyanate polymer		30-60%	
Aromatic hydrocarbon solvent	64742-95-6	<10%	R65
Ethyl acetate	141-78-6	<10%	R11,R36,R66,R67
N butyl acetate	123-86-4	<10%	R10, R66, R67
Methoxy propyl acetate	108-65-6	<10%	R10,R36
Hexamethylene-1,6- diisocyanate	822-06-0	<0.5%	R23,R36/37/38,R42/43

4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

Ingestion: Rinse mouth with water. Give water to drink. Do NOT induce vomiting. Seek immediate medical assistance.

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through a face mask. If breathing has stopped apply artificial respiration at once. In event of cardiac arrest, apply external cardiac massage. Seek medical advice.

Skin Contact: Wash contaminated skin with plenty of soap and water. Remove contaminated clothing and wash before re-use. If swelling, redness, blistering, or irritation occurs seek medical advice.

Eye Contact: Irrigate with copious quantities of water for 15 minutes. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Notes to physician:

Treat symptomatically.

5. Fire-fighting measures

Hazards from combustion: On burning may emit toxic fumes including those of carbon oxides, nitrogen oxides, isocyanate vapours and hydrogen cyanide.

Fire-fighting advice: Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Flammable liquid. May form flammable vapour mixtures with air. Avoid all ignition sources. Heating can cause expansion or decomposition of the material, which can lead to the containers exploding. If safe to do so, remove containers from the path of fire. Keep containers cool with water spray.

Suitable Extinguishing Media: Foam, dry agent (carbon dioxide, dry chemical powder).

Hazchem Code: 3[Y]E

6. Accidental release measures

Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

Methods for containment & clean up:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect in properly labeled containers and seal once product has hardened.

7. Handling and storage

Handling advice:

Avoid skin and eye contact and breathing in vapour. May form flammable vapour mixtures with air. All potential sources of ignition must be eliminated both in and near the work area. Do NOT smoke. Flameproof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed. Vapour may travel a considerable distance to a source of ignition and flash back.

Storage advice:

Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. Exposure controls/personal protection

Occupational Exposure Limits:

National occupational exposure limits

No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standards for constituents:

Xylene, TWA 50 ppm, 217 mg/m³

n-butyl acetate, TWA 150 ppm, 713 mg/m³, STEL 200 ppm, 950 mg/m³

Toluene, TWA 50 ppm, 188 mg/m³ skin

Ethyl acetate, TWA 200 ppm, 720 mg/m³

Isocyanates (as NCO), TWA 0.02 mg/m³, STEL 0.07 mg/m³ Sen

As published by the New Zealand Occupational Safety and Health Service (OSH).

Workplace Exposure Standards -

Time-Weighted Average (WES-TWA). The eight hour, time weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

Short Term Exposure Limits (WES-STEL). The 15 minute average exposure standard. Applies to any 15 minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA: both short term and eight hour, time weighted average exposures should be determined.

'Sen' notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to minute levels of that substance.

Skin notation - as the above Workplace Exposure Standards only take into consideration the inhalation component, care should be taken when interpreting results when a constituent has a 'Skin notation'.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept as low a level as is workable. Workplace Exposure Standards should not be used as fine dividing between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering Control Measures:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected.

Personal Protective Equipment:

Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. Physical and chemical properties

Physical state:	Viscous liquid
Colour:	Pale yellow
Solubility:	Negligible
Specific Gravity:	0.99
Flash Point (°C):	11°C
Flammability Limits (%):	Not available
Boiling Point/Range (°C):	Not available

10. Stability and reactivity

Stability: Stable under normal conditions.

Conditions to avoid: Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition and open flame. Reacts with moisture

Incompatible materials: Incompatible with oxidising agents

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is uncoordinated there is a greater likelihood of vomit entering the lungs and causing subsequent complications.

Eye contact: May be an eye irritant.

Skin contact: Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant or allergic contact dermatitis. A skin sensitiser.

Inhalation: Vapour may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and, if exposure is prolonged, unconsciousness. Inhalation of mists or aerosols can produce respiratory irritation and possible allergic reactions.

Toxicological Data:

No LD50 data available for product. The toxicity of the product may be attributed to the solvents it contains. Additive effects may occur with mixtures of solvents. Similar effects can occur where the consumption of alcohol is also involved.

For Toluene: Oral LD50 (rat): 5580 mg/kg, Dermal LD50 (rabbit): 14000 mg/kg, SKIN: (Draize): Mild to moderate irritant, EYES: (Draize): Mild Irritant

The major effects in humans following acute exposure to high concentrations (such as in deliberate sniffing or industrial accidents) are central nervous system dysfunction and narcosis. Under controlled conditions, inhalation of 50, 75 or 100 ppm of toluene for 4 to 6 hours was associated with headache and irritation. There are also numerous reports of altered central nervous system performance among humans inhaling 40 ppm to more than 100 ppm. Both bioassay tests and other available data (including two human studies) indicate that toluene is not carcinogenic. Based on available in-vivo data, studies of humans are inconclusive with regard to genotoxicity, while most in-vitro studies indicate negative results for toluene. While there have been some reported developmental effects in experimental animal testing involving toluene, studies do not provide evidence that toluene is teratogenic following inhalation.

12. Ecotoxicological information

Avoid contaminating waterways. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

13. Disposal considerations

Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

Empty containers:

Do not contaminate storm water with product or product washing. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via domestic recycling programmes may differ between local authorities. Check with your local council first.

14. Transport information

Road and Rail Transport

Classified as Dangerous Goods by NZS 5433:1999 Transport of Dangerous Goods on Land.

UN No: 1263

Class-primary 3 Flammable Liquid

Packing Group: II

Proper Shipping Name: PAINT RELATED MATERIAL

Hazchem Code: 3[Y]E

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1263, Class-primary: 3 Flammable Liquid, Packing Group: II

Proper Shipping Name: PAINT RELATED MATERIAL

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA)

Dangerous Goods Regulations for transport by air.

UN No: 1263, Class-primary: 3 Flammable Liquid, Packing Group: II

Proper Shipping Name: PAINT RELATED MATERIAL

15. Regulatory information

Classification: This material is hazardous according to the criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

ERMA Approval: HSR002662

Group Standard: Surface Coatings and Colourants (Flammable) Group Standard

Subclass 3.1 Category B (high hazard) - Flammable liquid

Subclass 6.1 Category D - Substances which are acutely toxic.

Subclass 6.3 Category A - Substances that are irritating to the skin.

Subclass 6.4 Category A - Substances that are irritating to the eye

Subclass 6.5 Category A - Substances that are respiratory sensitisers

Subclass 6.5 Category B - Substances that are contact sensitisers

16. Other information

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.