



# Material Safety Data Sheet

## 1. Identification of the substance/mixture and supplier

Product Name: **Watermarque 2K WB Primer Resin**

Recommended use: Resin component for Watermarque 2K WB Primer coating

Supplier: Uroxsys Ltd  
Street Address: 2 Stonedon Drive, East Tamaki, Auckland  
Telephone Number: +64 9 2740808  
Facsimile: +64 9 2740500  
Emergency Telephone: After hours phone 0800 867666 (or 09 3034580), quote reference: Uroxsys Helpline

## 2. Hazards identification

Not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

Not classified as Dangerous Goods by NZS 5433:1999 Transport of Dangerous Goods on Land.

## 3. Composition/information on hazardous ingredients

Acrylic copolymer neutralized in water-based emulsion	>60%	
Solvent naphtha	64742-95-6	<2%
2-butoxyethanol	111-76-2	<2%
monoethanolamine	141-43-5	<0.4%

## 4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

**Ingestion:** If swallowed, do NOT induce vomiting. Seek immediate medical assistance. Begin artificial respiration if breathing has stopped. Use mouth to nose rather than mouth to mouth.

**Inhalation:** Remove to fresh air.

**Skin Contact:** If skin or hair contact occurs, immediately remove contaminated clothing and clean skin and hair with plenty of soap and water.

**Eye Contact:** If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

**Notes to physician:**  
No information available.

## 5. Fire-fighting measures

**Specific Hazards:** Hazardous combustion gases may be formed: carbon monoxide.

**Fire-fighting advice:** Fire fighters to wear self-contained breathing apparatus and suitable protective clothing.

**Suitable Extinguishing Media:**  
Use water spray, foam, carbon dioxide or dry chemical powder.

## 6. Accidental release measures

Do not empty into drains. Ensure adequate ventilation/exhaust ventilation. Keep unauthorized persons away. Remove mechanically, cover residues with chemical binder or dry sand and store in closed containers. Collect in properly labeled containers.

## 7. Handling and storage

**Handling advice:** Avoid skin and eye contact.

**Storage advice:** Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from foodstuffs.

## 8. Exposure controls/personal protection

### Occupational Exposure Limits:

No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for constituent(s):  
2-butoxyethanol (skin) TWA 25ppm, 121mg/m<sup>3</sup>

### Engineering Control Measures:

Ensure ventilation is adequate. Keep containers closed when not in use.

### Personal Protective Equipment:

Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists or spraying, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

## 9. Physical and chemical properties

Physical state:	liquid
Colour:	white
Solubility:	miscible
Specific Gravity:	1.0
Flash Point (°C):	>94°C
Flammability Limits (%):	not available
Boiling Point/Range (°C):	100-200

## 10. Stability and reactivity

**Stability:** No decomposition products if used as intended.

## 11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label.

### Long Term Effects:

Over-exposure, especially when spraying coatings containing isocyanate without the necessary precautions entails the risk of concentration-dependent irritating effects on eyes, nose, throat and respiratory tract. Delayed appearance of the complaints and development of hyper-sensitivity are possible. Hypersensitive persons may suffer from these effects even at low isocyanate concentrations.

### Toxicological Data:

The product is considered to be harmless to health if used in the correct manner.

## 12. Ecotoxicological information

Do not allow to contaminate waters, wastewater or soil. Notify authorities if water supply is contaminated.

## 13. Disposal considerations

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

## 14. Transport information

### Road and Rail Transport

Not classified as Dangerous Goods by NZS 5433:1999 Transport of Dangerous Goods on Land.

### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

## 15. Regulatory information

This material is not hazardous according to the criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

## 16. Other information

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.