

**PROPELLERLEIM HÄRTER**

(Types F, B, J)

**Application areas:**

Propellerleim-Härter is an addition to Propellerleim-wood glues to increase the waterproofness. With the mixture wood glue/hardener, gluings of the encroachment group D4, according to the quality grade DIN/EN 204, can be achieved.

**Advantages:**

Propellerleim-Härter is easy to stir into the glue. The mixture achieves different pot lives. Please consider the leaflet of Propellerleim.

**Processing conditions:**

Mixture : 100 parts by weight Propellerleim  
: 5 parts by weight Propellerleim-Härter

**Storage**

At least 12 months durable, store dry and well closed in the original cask. In low temperatures, the Propellerleim Härter tends to crystallize. If the glue hardener crystallized, please heat up slowly to 20-30 C and loosen the crystals.

**Marking**

VbF : applicable  
GefStoffV: marking not compulsory  
GGVS : marking not compulsory

**Casks of supply:**

600 g bottle (12 bottles in carton)  
1,6 kg. canister  
25 kg canister  
150 kg barrel

**Service:**

Our counseling service for technical applications is ready to help you at any time without obligation.

**Phone:** +49 6384 99 38 - 0  
**Fax:** +49 6384 99 38 - 112  
**Email:** [info@rhenocoll.de](mailto:info@rhenocoll.de)

This information is given without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. In any case we recommend that users make their own tests since we have no influence over the large variety of materials and their use. No liability for the manufacturer can be derived from the contents of this notice.

Statements going beyond or deviating from the contents of this notice requires the written confirmation of the company headquarters.

In all cases our General Terms of trade and delivery are in effect.

With the appearance of this Technical Notice all previous versions become invalid.