

R H E N O C R Y L Colour Paint
R H E N O C O L O R Dyestuff W-FL

L-FL

L-PK

Waterbased

Application

Rhenocryl tinting paste can be used for the toning and tinting of Rhenocoll-varnishes and Rhenocoll-glazes according to the Rhenocoll colour system. Determined for the application in technical business enterprises.

Features

Rhenocryl tinting pastes are compatible with many other Rhenocoll-varnishes and Rhenocoll-glazes. The application is made by the Rhenocoll-mixing recipes.

Hints for application

Shake the pastes thoroughly before application. After adding the paste to the basis, shake the mixture again to homogenize it.

Specific gravity

1,1 – 2,3 g/cm³ depending on the paste.

Weather-stability

Depending on pigment type and mixing rate with titanium dioxide pigment. Classification stresses from „excellent“ to „good“.

Consumption

Tinting pastes can differ, depending on the tone. 1 liter tinting paste can be used for the tinting of 10 – 2000 liter basis paint.

Dilution

The pastes are ready for use, do not dilute.

Cleaning

Before hardening, remove dashes of tinting paste with water.

Storage

Storage life is about 12 months when stocked dry and closed. Storage temperature of 15 - 30 °C is recommended. Minimum temperature 1°C, maximum temperature 45°C, avoid higher temperatures. Protect against frost.

Safety Advice

Not inflammable. No identification.

Form supplied

500 ml bottle
1000 ml bottle
5 l bucket

Service:

Our counseling service for technical applications is ready to help you at any time without obligation.

Phone: +49 6384 99 38 - 0
Fax: +49 6384 99 38 - 112
Email: info@rhenocoll.de

This information is given without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. In any case we recommend that users make their own tests since we have no influence over the large variety of materials and their use. No liability for the manufacturer can be derived from the contents of this notice.

Statements going beyond or deviating from the contents of this notice requires the written confirmation of the company headquarters.

In all cases our General Terms of trade and delivery are in effect.

With the appearance of this Technical Notice all previous versions become invalid.